



Nota: da usare per termoidurenti

如图非标件（车削工艺），  
材质低碳钢+环保镀锌  
数量1000/3000/6000千件  
M4

散装15kgs，欧式托盘

**1. Designazione**

Inserto RT21552/...+...  
+ Porre l'indicazione per la designazione stabilita al punto 3.

**2. Descrizione dimensionale**

In mm.

**3. Dimensioni**

								Gruppo 87
								Famiglia 814055
Indicazione per la designazione	a	b	d	d1	D	Foratura diametro (raccomandato)	Foratura Spessore Parete min.	Codice
M3-A*	0.58	4	M3	4.7	4.2	4	2	RP0725001
M3	0.58	5.3	M3	4.7	4.2	4.1	2	RP0151001
M4	0.80	7.4	M4	7.2	5.8	5.4	2.5	16249
M4-A*	0.89	7.42	M4	6.8	5.8	5.4 <sup>0.075</sup> <sub>0</sub>	2.5	RP0078001
M5	1.07	8.33	M5	7.9	6.6	6.2	2.5	RP0014001

\*Dimensioni non standard

**4. Materiale**

Ottone.

**5. Filettatura**

Metrico ISO a passo grosso, destra secondo UNI 4535.



ELSP	A	ECN000236371		
R&D	B	ECN000287925		
Competence Center Italy	C	ECN000287925		

**SUPPLY  
INFORMATION**
**Use**

Designation information	EQUIPMENT SWITCHBOARD	Notes

**Acceptance check**

Visual and dimensional check.

**Approved suppliers**

Designation indication	SUPPLIERS AND RESPECTIVE CORRESPONDING TYPES		
M3-A	HSR B M3x4 HD 4,7		
M3	HSR B M3x5,3		
M4	HSR B M4x7,4		
M4-A	HSR B M4x7,42		
M5	HSR B M5x8,33		

**Ordering description**

Designation as in section 1 and onwards, in compliance with our enclosed table.

ELSP	A	ECN000236371	
R&D Competence Center Italy	B	ECN000287925	
	C	ECN000287925	