



如图（汽配质量标准），  
 需提供产前样，不能做  
 PPAP3工厂勿扰，  
 100%光学挑选50PPM无异物

材质C4C，表面环保镀锌不低于12um  
 数量100千件，  
 散装15kgs，欧式托盘

- AUTOMOTIVE CUSTOMER
- SAMPLING + PPAP LIV III
- 100% SORTING FOR MIXED PARTS + PRESENCE OF THREAD - 50PPM
- MATERIAL / SURF. TREATMENT AS DRW SPECIFIED
- NO DEVIATION ADMITTED (in case specify it clearly)

SPECIFICHE TECNICHE - TECHNICAL SPECIFICATIONS

1- * QUOTE REALI	5- □ QUOTE CRITICHE
2- ( ) QUOTE NON FUNZIONALI	6- AMMESSA BAVA SUI BORDI TAGLIATI MAX 0.1 mm.
3- □ QUOTE DI RIFERIMENTO	
4- ⊕ QUOTE FUNZIONALI SECONDARIE	

MODIFICHE	□	○	□
EMMISSIONE	27/1/09	27/1/09	27/1/09

**RISERVATO  
 RESERVED**

DISEGNATO A.M.	DATA 16/9/98*	CONTROLLATO A.M.	DATA 27/1/09	EMMISSIONE 27/1/09
----------------	---------------	------------------	--------------	--------------------

SUPERFICIE (ZINC.BIANCA) Fe/Zn12II(CRVI esente)

MATERIALE SIGLA ACCIAO C4C UNI EN 10263-2

RIFERIMENTO CLIENTE		TOLLERANZE ±0.2	SCALA 5:1
---------------------	--	-----------------	-----------

DESCRIZIONE RIVETTO PER PATTINO	PEZZO N° 2985.00.004	IND.MOD. A
	OPPOSTO SYMM.OPP.	A4

A REVISIONE GENERALE - SOST - MAT.era 9SMnPb23 - 27/1/09 - A.M.